

A modernized take on a forestry-proven classic design and go-to attachment for land clearing contractors who want to turn larger trees in to a consistent finished product using a familiar, fully boxed-in, high strength unit for excavators. The HD Series design is known to last 20+ years.







KEY SPECS:	HDM 36	HDM 48	HDM 60
EXCAVATOR SIZE (TONS)		MIN: 20 MAX:30+	MIN: 22 MAX:30+
CUT WIDTH (INCHES)	36	48	60
MIN. WEIGHT (POUNDS)	2600 (FLAT-TOP BRACKET)	2900 (FLAT-TOP BRACKET)	3200 (FLAT-TOP BRACKET)
n STD. MOTOR TYPE	FIXED DISPLACEMENT	FIXED DISPLACEMENT	FIXED DISPLACEMENT
🔹 STD. MOTOR SIZE (CC)	80	107	107
💧 AVG. FLOW RANGE (GPM)	32-36	40-44	40-44
MIN. PRESSURE (PSI)	4000	4000	4000
Ø SUGGESTED DRUM SPEED (RPM)	2200	2200	2200

INDUSTRIAL CONTRACTOR'S CHOICE

BUILD & COMPONENTS

STANDARD

DESIGN

"FIXED TOOTH ROTOR" DRUM TYPE

20" FRONT

EXPOSED DRUM

EASILY ACCESSIBLE SERVICE POINTS FLAT-TOP BRACKET

REPLACABLE

WEAR SHOES

FULLY BOXED-IN

CONSTRUCTION

OPTIONAL

BRACKET MOUNTED PUSHER PAD QUAD OR CARBIDE Tooling

QUICK CHANGE OR PIN TYPE BRACKET FIXED OR VARIABLE DISPLACEMENT MOTOR

USE CASES

RIGHT-OF-WAY CLEARING

INDUSTRIAL PROPERTY Development INDUSTRIAL MAINTENANCE



🚺 1-833-577-1847 🍈 PROMACEQUIPMENT.CA